

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version	Revision Date:	Date of last issue: 03.02.2021
2.1 GB / EN	26.08.2021	Date of first issue: 27.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Yachtcare Polyglas VT Repair Kit No.0
Product code : 154.231

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Resins
Recommended restrictions on use : public use, professional use, Industrial use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH
Esinger Steinweg 50
25436 Uetersen
Germany
info@vosschemie.de
Telephone : 04122 717 0
Telefax : 04122 717158
Responsible Department : Laboratory
04122 717 0
sds@vosschemie.de

1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,
Göttingen, Deutschland
0551 19240

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version
2.1

GB / EN

Revision Date:
26.08.2021

Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Warning

Hazard statements

: H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved facility in

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version
2.1

GB / EN

Revision Date:
26.08.2021

Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

accordance with local, regional, national and international regulations.

Additional Labelling

EUH208 Contains Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Resin

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
vinyltoluene	25013-15-4 246-562-2 01-2119622074-50, 01-2120106403-73	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 30
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Not Assigned 911-490-9 01-2119979579-10	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0.25 - < 1
1,4-dihydroxybenzene	123-31-9 204-617-8 604-005-00-4 01-2119524016-51	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 2; H351 Aquatic Acute 1; H400	>= 0.0025 - < 0.025

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

		Aquatic Chronic 1; H410	
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : First aider needs to protect himself.
Remove from exposure, lie down.
Symptoms of poisoning may appear several hours later.
Victim to lie down in the recovery position, cover and keep him warm.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
Call a physician immediately.
- In case of skin contact : Wash off with warm water and soap.
Remove contaminated clothing and shoes.
Wash contaminated clothing before reuse.
If skin irritation persists, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult a physician.
- If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version	Revision Date:	Date of last issue: 03.02.2021
2.1	26.08.2021	Date of first issue: 27.09.2019

Water spray jet
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use water spray to cool unopened containers.
In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
Use personal protective equipment.
Remove all sources of ignition.
Contaminated surfaces will be extremely slippery.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version
2.1

GB / EN

Revision Date:
26.08.2021

Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not get on skin or clothing.
Avoid contact with eyes.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid breathing vapours, mist or gas.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Vapours may form explosive mixture with air. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. No sparking tools should be used.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep tightly closed in a dry and cool place. Store in original container. Keep in a well-ventilated place. Keep away from heat and sources of ignition. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.
Incompatible with oxidizing agents.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Workers	Inhalation	Long-term systemic effects	9.8 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1.4 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2.9 mg/m ³
	Consumers	Skin contact, Oral	Long-term systemic effects	0.83 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction mass of 2,2'-[(4-	Fresh water	0.048 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-		
	Marine water	0.005 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1.2 mg/kg
	Marine sediment	0.12 mg/kg
	Soil	0.21 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : >= 0.7 mm
Directive : DIN EN 374
Protective index : Class 6

Material : Viton®
Break through time : > 480 min
Glove thickness : >= 0.7 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection Butyl gloves are not suitable. Avoid natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Respirator with combination filter for vapour/particulate (EN 141)

Filter type : Type A (A)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version	Revision Date:	Date of last issue: 03.02.2021
2.1	26.08.2021	Date of first issue: 27.09.2019

GB / EN

Avoid contact with the skin and the eyes.
Wear suitable protective equipment.
Follow the skin protection plan.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	viscous liquid
Colour	:	amber
Odour	:	aromatic
Melting point/freezing point	:	-76.8 °C Literature value vinyltoluene
Boiling point/boiling range	:	168 °C Literature value vinyltoluene
Upper explosion limit / Upper flammability limit	:	6.1 %(V) Literature value vinyltoluene
Lower explosion limit / Lower flammability limit	:	1.9 %(V) Literature value vinyltoluene
Flash point	:	53 °C Literature value vinyltoluene
Ignition temperature	:	575 °C Literature value vinyltoluene
pH	:	not determined substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	2 hPa (20 °C) Literature value vinyltoluene
Density	:	1.1 g/cm ³

9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapour-air mixture.
------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version	Revision Date:	Date of last issue: 03.02.2021
2.1 GB / EN	26.08.2021	Date of first issue: 27.09.2019

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Polymerisation can occur.
Reacts violently with peroxides.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Keep away from heat and sources of ignition.
Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong oxidizing agents
polymerisation initiators
Copper
Copper alloys
Brass

10.6 Hazardous decomposition products

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

vinyltoluene:

Acute oral toxicity : LD50 Oral (Rat): 3,680 mg/kg
Acute inhalation toxicity : LC50: 16.861 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): 4,490 mg/kg

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Acute oral toxicity : LD50 Oral (Rat): 619 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

1,4-dihydroxybenzene:

Acute oral toxicity : LD50 Oral: > 375 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

vinyltoluene:

Assessment : Irritating to skin.
Result : Skin irritation

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

vinyltoluene:

Assessment : Irritating to eyes.
Result : Moderate eye irritation

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 429
Result : positive

1,4-dihydroxybenzene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 429
Result : positive

Germ cell mutagenicity

Not classified based on available information.

Components:

1,4-dihydroxybenzene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Genotoxicity in vivo : Species: Mouse (males)
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 483
Result: positive

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

1,4-dihydroxybenzene:

Effects on foetal development : Species: Rat
Application Route: Oral
Dose: 0 - 30 - 100 - 300 milligram per kilogram
General Toxicity Maternal: NOAEL: 100 mg/kg body weight
Developmental Toxicity: NOAEL: 100 mg/kg body weight
Method: OECD Test Guideline 414

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version
2.1

GB / EN

Revision Date:
26.08.2021

Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

Result: negative
Fertility and developmental toxicity tests did not reveal any effect on reproduction.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

vinyltoluene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

vinyltoluene:

Toxicity to fish : LC50 (Fat head minnow): 5.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.3 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2.6 mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.6 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 1.16 mg/l
Exposure time: 30 d
Species: Fish

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.32 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

1,4-dihydroxybenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.638 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.134 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 0.33 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to fish (Chronic toxicity) : NOEC: \geq 0.1 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210

Toxicity to daphnia and other : NOEC: 0.0057 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

aquatic invertebrates (Chronic toxicity) Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

1,4-dihydroxybenzene:

Biodegradability : Result: rapidly biodegradable
Biodegradation: 70 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

12.3 Bioaccumulative potential

Components:

vinyltoluene:

Bioaccumulation : Species: Fish
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 3.58

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Partition coefficient: n-octanol/water : log Pow: 2.17 (20 °C)

1,4-dihydroxybenzene:

Bioaccumulation : Bioconcentration factor (BCF): 40

Partition coefficient: n-octanol/water : log Pow: 0.59

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. Send to a licensed waste management company. Do not dispose of with domestic refuse. Do not empty into drains; dispose of this material and its container in a safe way.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product. Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
07 00 00, WASTES FROM ORGANIC CHEMICAL PROCESSES
07 02 00, wastes from the MFSU of plastics, synthetic rubber and man-made fibres
070299, wastes not otherwise specified

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1866
ADR : UN 1866
RID : UN 1866
IMDG : UN 1866
IATA : UN 1866

14.2 UN proper shipping name

ADN : RESIN SOLUTION
ADR : RESIN SOLUTION

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version 2.1 GB / EN Revision Date: 26.08.2021 Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

RID : RESIN SOLUTION

IMDG : RESIN SOLUTION

IATA : Resin solution

14.3 Transport hazard class(es)

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

ADR

Packing group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366

Packing instruction (LQ) : Y344

Packing group : III

Labels : Class 3 - Flammable liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355

Packing instruction (LQ) : Y344

Packing group : III

Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version	Revision Date:	Date of last issue: 03.02.2021
2.1	26.08.2021	Date of first issue: 27.09.2019

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version	Revision Date:	Date of last issue: 03.02.2021
2.1 GB / EN	26.08.2021	Date of first issue: 27.09.2019

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H341	: Suspected of causing genetic defects.
H351	: Suspected of causing cancer.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Muta.	: Germ cell mutagenicity
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

Yachtcare Polyglas VT Repair Kit No.0

Version
2.1

GB / EN

Revision Date:
26.08.2021

Date of last issue: 03.02.2021
Date of first issue: 27.09.2019

International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.