

Sikaflex®-290 DC PRO THE PROFESSIONAL DECK CAULKING SEALANT

- Sandable, that's easy and fast
- **■** Excellent weathering resistance
- Robust and durable
- Professional use only
- **■** IMO certified



Sikaflex®-290 DC PRO

Sikaflex®-290 DC PRO is a 1-component polyurethane based joint sealing compound, specifically formulated for caulking joints in traditional timber marine decking. It exhibits excellent weathering resistance and is therefore well suited for highly exposed open joints within the marine environment.

For specific applications consult the product data sheet or contact your Sika Technical Service.

PRODUCT BENEFITS

- **■** Flexible
- Well suited for highly exposed open joints
- Long toolability
- Resistant to seawater and fresh water

AREAS OF APPLICATION

- Caulking of joints in traditional timber decking
- Boats, yachts, commercial ships



Typical Product Data	
Chemical base	1-C Polyurethane
Cure mechanism	Moisture curing
Density (uncured) (CQP006-4)	1.3 kg/l
Application temperature	5 - 35°C
Skin time (CQP019-1)	90 minutes approx ^A
Shore A hardness (CQP023-1/ ISO 868)	40
Tensile strength (CQP020-3)	3 MPa
Elongation at break (CQP020-3)	600% approx
Shelf life (storage below 25°C) (CQP016-1)	9 months for pail

CQP = Corporate Quality Procedure A23°C/50% r.h

Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.









SIKA LIMITED

Head Office Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ United Kingdom

SIKA IRELAND LIMITED

Sika House Ballymun Industrial Estate Dublin 11 D11 DA2V Ireland

Contact

Phone +441707394444

E-Mail sealing and bonding enquiries @uk.sika.com

www.sika.co.uk/sealantsandadhesives

@SikaLimited

Contact

Phone +353 1 862 0709 Fax +353 1 862 0707 E-Mail info@ie.sika.com

www.sika.ie

Sikalreland

