



IMPIEGO

Tube in gomma long length idoneo per adduzione di olii minerali, diesel e benzine ecologiche.

- **Temperatura:** -35°C +90°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera NBR resistente ai prodotti petroliferi con contenuto aromatico non superiore del 50%.
- **Rinforzi:** inserzioni di filati sintetici ad alta resistenza.
- **Copertura:** in gomma nera nitrilica antistatica (R<1M □/m) resistente all'abrasione, ai carburanti, agli olii e agli agenti atmosferici.
- **Superficie:** liscia estrusa.
- **Marcatura:** ad inchiostro "H.T. - CARBUPOMP/10NL - W.P. 10 BAR - R < 1 M □/m - ISO R 1307"

Disponibili su richiesta:

CARBUPOMP/10NL/ZINC: con rivestimento in calza di acciaio zincato.

CARBUPOMP/10NL/INOX: con rivestimento in calza di acciaio inox.



APPLICATION

Long length rubber hose suitable for loading of mineral oils, diesel and unleaded fuel.

- **Temperature range:** -35°C +90°C

CONSTRUCTION

- **Tube:** black, smooth, petroleum products up to 50% aromatic NBR rubber.
- **Reinforcement:** high strength synthetic textile yarn.
- **Cover:** black, abrasion, fuels, oils and weathering resistant nitrilic antistatic rubber (R<1M □/m).
- **Surface:** smooth extruded.
- **Branding:** ink marking "H.T. - CARBUPOMP/10NL - W.P. 10 BAR - R < 1 M □/m - ISO R 1307"

Available on request:

CARBUPOMP/10NL/ZINC: galvanized steel wire braid cover.

CARBUPOMP/10NL/INOX: stainless steel wire braid cover.

DIAMETRO INTERNO INSIDE DIAMETER		SPESSORE THICKNESS		PESO TEORICO WEIGHT		PRESSIONE ESER- CIZIO		PRESSIONE SCOPPIO BURST PRESSURE		RAGGIO DI CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	mm	inch	gr/mt	lbs/ft	bar	psi	bar	psi	mm	inch	mt	ft
O.B. MOTOR/HOSE													
5	3/16"	12	15/32"	0.13	0.09	10	150	30	450	40	1.57"	50/100	164/328
6	1/4"	12	15/32"	0.12	0.08	10	150	30	450	50	1.97"	50/100	164/328
7	5/18"	13	1/2"	0.13	0.09	10	150	30	450	55	2.17"	50/100	164/328
8	5/16"	15	19/32"	0.18	0.12	10	150	30	450	65	2.56"	50/100	164/328
10	3/8"	17	21/32"	0.21	0.14	10	150	30	450	80	3.15"	50/100	164/328
CARBUPOMP/10NL													
13	1/2"	20	25/32"	0.26	0.17	10	150	30	450	105	4.13"	50/100	164/328
15	19/32"	23	29/32"	0.34	0.23	10	150	30	450	120	4.72"	50/100	164/328
16	5/8"	24	15/16"	0.31	0.21	10	150	30	450	130	5.12"	50/100	164/328
19	3/4"	27	1.1/16"	0.40	0.27	10	150	30	450	150	5.91"	50	164
25	1"	35	1.3/8"	0.66	0.44	10	150	30	450	200	7.87"	50	164