



3nm 225° Masthead, silver anodized, vertical mount, with 0,7m cable

201-011

3nm masthead, silver anodized
Vertically mounted with 0,75m cable

Specifications	
Number	201-011
Light Color	White
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009707
IP rating	IP68
Power draw (W)	3
UPC Code	879343009700
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	232
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	127
Vessel size	12-20M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.43 Kg
Weight (Oz)	15.17 Oz